



HXE110-KP

Smart Single Phase Prepayment Residential Meter

HXE110-KP is a smart single phase prepayment residential meter with keypad to provide local and remote reading, writing and credit charging through STS standard and varying plug-play communication modules

STS

STS standard

CTS

CTS standard



Built-in relay control

P \rightleftharpoons P

Prepaid / Post-paid switch



Import and export measurement



Multiple communication



Demand Monitoring



Anti-tamper

MD

Maximum demand






Load profile



Local and remote charge



CIU



TECHNICAL SPECIFICATION

ACCURACY	Active:	Class 1(IEC) / Class B (MID)
NOMINAL VOLTAGE	1 phase 2 wire	110V...240V
CURRENT RANGE	I _b / I _{ref} I _{max}	5A, 10A, 80A, 100A
STARTING CURRENT	According to IEC	0.4%I _b
FREQUENCY		50 / 60Hz
POWER CONSUMPTION	Phase voltage Voltage circuit : Current circuit :	230V < 1W, < 5VA < 0.1VA
TEMPERATURE RANGE	Operation: Storage:	- 25 ° C to +55 ° C - 40 ° C to +70 ° C
HUMIDITY RANGE		Up to 95%
PROTECTION DEGREE		IP54 (indoor)
EMC	Surge (1.2 / 50 μs) EMC environmental conditions	6KV acc.IEC 62052-11
RTC	Clock Accuracy	< 0.5s / day
STANDARDS	IEC standard MID standard	IEC 62052-11 IEC 62053-21 EN54070-1 EN54070-3
COMMUNICATION	Built-in Modules (optional)	Optical, RS485 / MC171 / M-BUS 2G / 3G / PLC / RF-Mesh / Ethernet
OUTPUT/INPUT	1 x Electronic outputs (optional)	acc.IEC 62053-31
DATA STORAGE	Load profile (optional) Billing data	8 channels 12 Billing periods
TERMINALS		BS7856
BATTERY		Exchangeable
DISCONNECTOR	Maximum switch voltage Maximum switch current Short circuit ≤10ms Mechanical life Electrical life	250V 100A 3000A (according to IEC62053-21) ≥ 300000 OPS ≥ 10000 OPS
HOUSING MATERIAL		Polycarbonate+GF

 **HEXING** | www.hxgroup.cn

Headquarter: 1418-5 Moganshan Road, Shangcheng Industrial Zone,
310011, Hangzhou City, China
Tel: + 86 571 2802 07 67 Fax: +86 571 2802 92 63
Email: market@hxgroup.co



Scan Here to Discover More